



hp LaserJet 2200 series printers

## **User Guide**

## HP Customer Care (Service and Support)

---

### HP Customer Care (Service and Support)

---

<b>Online Services:</b> for 24-hour access to information over your modem, we suggest these services:	<b>World Wide Web URL</b> - Printer drivers, updated HP printer software, plus product and support information may be obtained from the following URLs: English language site <a href="http://www.hp.com/go/support">http://www.hp.com/go/support</a> in the U.S. <a href="http://www.hp.com">http://www.hp.com</a> in Europe <a href="http://www2.hp.com">http://www2.hp.com</a> Printer drivers may be obtained from the following sites: in Japan <a href="http://www.jp.hp.com/drivers/">http://www.jp.hp.com/drivers/</a> in Korea <a href="http://www.hp.co.kr">http://www.hp.co.kr</a> in Taiwan <a href="http://www.hp.com.tw">http://www.hp.com.tw</a> or the local driver website <a href="http://www.dds.com.tw">http://www.dds.com.tw</a>
---	---

# A Specifications

## Printer Specifications

	HP LaserJet 2200	HP LaserJet 2200 with Optional Tray 3 (250-sheet)	HP LaserJet 2200 with Optional Tray 3 (500-sheet)
Height	255 mm (10.0 in.)	334 mm (13.2 in.)	395mm (15.6 in.)
Width	405 mm (16.0 in.)	405 mm (16.0 in.)	405 mm (16.0 in.)
Depth (body)	435 mm (17.1 in.)	435 mm (17.1 in.)	435 mm (17.1 in.)
Weight (with toner cartridge)	14.0 kg (29.0 lbs)	17.1 kg (35.9 lbs)	18.7 kg (39.4 lbs)

Electrical Specifications	110-Volt Models	220-Volt Models
Power Requirements	100-127V (+/- 10%) 50/60 Hz (+/- 3 Hz)	220-240V (+/- 10%) 50/60 Hz (+/- 3 Hz)
Minimum recommended circuit capacity for typical product	5.0 Amps	2.5 Amps
Average Power Consumption (Watts) - HP LaserJet 2200 series printers	Printing (18 PPM) = 400 W Standby = 12 W PowerSave = 12 W Off = 0 W	Printing (18 PPM) = 400 W Standby = 12 W PowerSave = 12 W Off = 0 W

PowerSave default activation time is 15 minutes.  
Values are subject to change. See <http://www.hp.com/support/lj2200> for current information.

**WARNING!** Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This may damage the printer and void the product warranty.

Environmental Specifications	Operating Printing	Storage/Standby
Temperature (printer and toner cartridge)	15° to 32.5° C (59° to 89° F)	-20° to 40° C (-4° to 104° F)
Relative humidity	10% to 80%	10% to 90%

Acoustic Emissions (HP LaserJet 2200)	Bystander Position	Declared Per ISO 9296
	Printing (18 PPM)	$L_{pAm} = 51 \text{ dB(A)}$
	PowerSave	Essentially inaudible
	<b>Sound Power</b>	<b>Declared Per ISO 9296</b>
	Printing (18 PPM)	$L_{WA,d} = 6.6 \text{ bels(A)}$
	PowerSave	Essentially inaudible

You may wish to place printers with sound power equal to or greater than 6.3 bels in a separate room or cubicle. Values are subject to change. See <http://www.hp.com/support/lj2200> for current information.



copyright © 2001  
Hewlett-Packard Company

[www.hp.com/support/lj2200](http://www.hp.com/support/lj2200)

english



C7058-90956

4156

---